

TUNNEL GUBRIST, 3RD TUBE



New construction 3rd tube Tunnel Gubrist, Zurich, Switzerland

The construction of the 3rd tube Tunnel Gubrist is the centrepiece of the expansion of the northern bypass in Zurich.

Scope

- The new construction of the 3rd tube Tunnel Gubrist has a total length of 3.3km. Of these, 3'010m will be created as a mining tunnel and about 300m as a cut-and-cover tunnel
- On the side Weiningen joins the portal to a 100m long overlap
- The tunnel is connected to the existing second tube with 12 cross-sections (accessible and passable)
- The lining is double-shell with drained partial seal (umbrella seal)
- 3 operating centers are planned, one of which will be built underground around the lay-by
- 2 central ventilation units with smoke exhaust system at the portals Affoltern and Weiningen
- The execution is carried out by blast heading

Amberg Services

- SIA project phases 32 to 53 (Preliminary design to commissioning)
- Overall responsible project manager, project manager of sub-projects and site supervision
- Planning & Design of all underground structures
- Within JV, planning & design and coordination of the sub-projects tunnel, cut-and-cover / construction pit, installation sites / loading bay, Cover Weiningen.
- Application of departments of the Federal Roads Office ASTRA: tunnel/geotechnics, engineering structure, alignment/environment, operating and safety equipment/installations
- Ventilation Design, Geology from tender design
- Coordination of interfaces with adjacent subprojects (lots 1,3,4)
- Coordination with further consultants (Fit-out, Environment, Traffic, Architects)
- Coordination with Operations, city and canton of Zurich, municipalities, AXPO and SBB

CHALLENGES

- Up to and including tender design (SIA 32-41) the project is planned & designed with the TBM-S excavation method (Ø15.7m) with segmental lining, conventional excavation with drill & blast and a machine-assisted excavation with pilot tunnel (Ø5.0m)
- The tunnel lining consists of an outer steel fibre sprayed concrete lining, rock bolts, umbrella waterproofing membrane and an unreinforced in-situ concrete secondary lining
- Planning & Design services are carried out in compliance with current standards, safety standards and ASTRA specifications regarding operation and safety
- Application of the ASTRA areas of tunnel/geology, tunnel/environment and engineering structures
- Project in focus of the public, politics and environmental organizations
- Construction under operation (the two neighbouring tunnels remain in operation during the entire construction period)
- Extensive traffic planning
- Portal Weiningen in the middle of a residential area.
- Considerations of vibrations, noise and structure-borne noise around the existing facility and in the residential area
- Integration of noise protection measures at the portals
- Complex construction site logistics and stringent requirements on material management (railbound muck handling facility)
- Extensive earthworks and concrete work
- The development of the northern bypass carried out in vicinity of moor biotopes
- Conducting drill & blast trials
- Evaluation of swelling tests (marl)
- Modelling execution design in 3D (BIM)

ENGINEERING APPROACH



Driven portal side Affoltern

Main drive Affoltern

- The main excavation face of the mined tunnel is commenced from Affoltern
- The excavation is carried out with a heading advance, followed with bench and invert.
- Drill & Blast excavation method
- Machine-aided excavation in rock



Dismantling bench using a rock cutter

TECHNICAL SOLUTIONS



Driver portal side Weiningen


Support measures

- The tunnel advance of the mined tunnel in Weiningen heads into the opposite direction challenged with low overburden.
- In order to minimize settlement in the urbanised area, five (5) pipe umbrella advances (l= 15m) with subsequent spiles (l= 30m) were constructed.




Installation pipe screen

CHALLENGES



■ Modelled situation




■ New traffic regime




■ Execution lid construction Weitingen

ENGINEERING APPROACH



■ Underground operations centre, 3D model (BIM)




■ Combined SOS and hydrant niches



■ Loading station, material management


TECHNICAL SOLUTIONS



■ Normal profile (TBM-drive)



■ Service tunnel elements (WLK)



■ Overview of operating and ventilation centres