

# STUTTGART 21



## Stuttgart 21, Railway Tunnel, Germany

Construction of the new railway Filder Tunnel (PFA 1.2) and the tunnels towards Ober- / Untertürkheim (PFA 1.6a/b)

### Scope

- Tunnel in urban surroundings
- Inner diameter of 8.10 m to 9.40 m
- Length of all tunnels approx. 30 km
- Branch-off structures and flyovers as well as an underground crossing of the river Neckar

### Challenges

- The tunnel is passing through layers of undrained anhydrite-bearing Keuper gypsum (highly swelling conditions), drained Keuper gypsum, reed sandstone,
- Upper / Lower coloured marls, German Stubensandstein, nodule marls as well as Lias formations
- The strata is bearing mineral water in parts

### Amberg Services


- Preliminary design for alternatives with shotcrete lining method and TBM heading method
- Tender Design and preparation of Tender documents for both methods



■ Layout of tunnel projects



■ Railway section at Filder



■ Inner lining

## AMBERG FACTS

### Contracted value JV

- Total JV 19.5 Mio. €

### Contracted value Amberg

- Total 3.6 Mio €

### Project Phases & Duration

- Elaboration of preliminary design 2008
- Elaboration of tender 2010
- Realisation since 2011

### Project Details

- Conventionally driven tunnel in urban surroundings and formation with high swelling potential
- Inner diameter of 8.10 m to 9.40 m
- Total length of all tunnels approx. 30'000 m
- Inner Lining up to 100 cm (due to swelling conditions)
- Overburden up to 220 m
- Undercrossing the river of Neckar with an overburden of only 6 m
- Distance between the different tunnel tubes at the flyovers down to only 1 m
- Downtown access adit to the tunnel works with a 22 m deep vertical shaft
- Caverns up to 180 m<sup>2</sup> for TBM installation
- Design of water partitioning structures to stop water flow along the tunnel (to reduce swelling potential)

## CLIENT FACTS

### Overall costs

- Total 2'000 Mio. €

### Project Overview

- Construction of a railway tunnel in lot PFA 1.2 (Filder Tunnel) and PFA 1.6a/b (Tunnel to Ober- / Untertürkheim), inclusive of all branch-off structures and flyovers as well as an underground crossing of the river Neckar

### Geology

- The tunnel is passing through layers of undrained anhydrite bearing Keuper gypsum, drained Keuper gypsum, and reed sandstone, upper / Lower coloured marls, German Stubensandstein, nodule marls as well as Lias α. The strata are bearing mineral water in parts

### Contact person

DB Project Stuttgart-Ulm GmbH (German Railways), Stuttgart, Germany

Mr Jochen Lutz

Phone: +49 711 933 19-425

Email: jochen.j.lutz@deutschebahn.com

## AMBERG KEY PEOPLE INVOLVED



**Paul Erdmann**  
Civil Engineer  
Project Manager

[perdmann@amberg.ch](mailto:perdmann@amberg.ch)



**Dr Roman Wahlen**  
Civil Engineer  
Deputy Project Manager

[rwahlen@amberg.ch](mailto:rwahlen@amberg.ch)



**Michael Rehbock-Sander**  
Civil Engineer  
Expert and Overall Project Manager

[mrehbock@amberg.ch](mailto:mrehbock@amberg.ch)